

Teleflex[®] SX-1

Portable Radar/Time Domain Reflectometer



- Standalone operation or operation in conjunction with surge wave generators (thumpers)
- Single jog dial operation with piechart interface and No-User-Intervention Auto mode
- ARM[®] Multishot technology with 15 fault traces per arc reflection measurement
- ProRange distance-dependent exponential de-attenuation for significantly improved images of far-away reflections
- Supports all existing HV prelocation methods
- Auto-ranging cable end recognition, Auto-find cursor to fault position
- Rugged, robust, outdoor field-ready case

DESCRIPTION

The **Teleflex[®] SX-1** is a portable 2-channel cable radar or time domain reflectometer (TDR), designed to provide quick, effective, accurate and safe prelocation of faults in cable installations.

The instrument is operated via a **single jog dial** and an intuitive, well-proven **piechart user interface**. Its large and bright colour display with touchscreen functionality further enhances operator comfort and supports quick and accurate field work. A **Linux-based operating system** provides the highest standard of stability and reliability.

The Teleflex SX-1 is powered from its internal rechargeable battery and may be operated in battery only mode or via smart charger connected to a mains power supply.

It is housed in a rugged, robust, field-proven case making it suitable for use in hostile or challenging environments.

The **ProRange technology** is a distance-dependent exponential de-attenuation mode. It counteracts the exponential attenuation caused by the cable's filter characteristics, and thus ProRange greatly improves distant reflections without distorting the near field. It is a very beneficial feature for cables with many joints (splices), for very long cables, and for cables with high attenuation.

By combining the Teleflex SX-1 with a surge wave generator (thumper) and a separation device, all methods of high voltage fault prelocation become accessible. The Teleflex SX-1 is compatible with all fault location units, and the **ΔU Trigger technology** always provides the most optimally timed trigger.

The **ARM[®] Multishot technology** is capable of capturing 15 fault traces per arc reflection measurement, of which the operator can select the best trace. This is particularly beneficial on wet faults, PLC cables, and longer cables.

The standalone software package **Reporting Edition** is available for the Teleflex SX-1. The Reporting Edition allows for import, analysis and protocol printing of stored TDR traces.

Teleflex® SX-1

Portable Radar/Time Domain Reflectometer

TECHNICAL DATA

Display	Industrial grade colour TFT panel
LCD size	10.1"
Aspect ratio	16:10
Resolution	1.280 x 800 (WXGA)
Backlight	LED
Luminance	1000 cd/m ² directly bonded
Pulse generation	Unipolar
Pulse amplitude	50 V fixed
Pulse width	20 ns ... 10 µs
Measuring range X_r	20 m ... 160 km at VOP = 80 m/µs
Resolution	0.1 m at VOP = 80 m/µs
Accuracy	0.1%
Timebase accuracy	Better than 100 ppm
Data rate	Faster than 400 MHz
Dynamic range	More than 96 dB
ProRange	More than +22 dB (distance-dependent de-attenuation)
Velocity of propagation	10 ... 149.9 m/µs VOP settable to m/µs or ft/µs or nvp
Output impedance	50 Ω No dedicated internal compensation necessary
ARM® trigger	ΔU trigger technology with automatic adjustment
External voltage	< 400 V, only with separation filter
Memory	4 GB for program and data
Connections	USB, BNC, CAN
Protection class	IP 65 enclosed, IP 54 open
Battery	12 V Li-Ion rechargeable battery Overload protection Deep Discharge protection Smart charger 110 ... 240 V, 50/60 Hz 10 ... 17 V DC, 3.8 A 6 hrs of operating time on full charge 4 hrs recharge time
Dimensions (W x H x D)	362 x 195 x 305 mm (14.2 in. x 7.6 in. x 12 in.)
Weight	7,8 kg (17.1 lbs)
Operating temperature	-10 °C ... +50 °C (14 °F ... +122 °F)
Storage temperature	-20 °C ... +60 °C (-4 °F ... +140 °F)

THE TELEFLEX SX-1 SUPPORTS THE FOLLOWING FAULT LOCATION TECHNOLOGIES:

- All arc reflection methods
- ARM® Multishot, ARM® Burning (Live Burn Arc Reflection)
- ICE (impulse current decoupling) and Loop On Loop Off
- DECAY (voltage decoupling)
- Phase comparison and Difference measurement
- Symmetrical and unsymmetrical measurement
- IFL mode for intermittent faults
- Partial discharge pinpointing

BENEFITS AND FEATURES AT A GLANCE

- Large 10.1" sunlight readable touchscreen colour display
- Very easy to operate because of its intuitive and straightforward piechart user interface
- Automatic smart measurement mode with no user intervention necessary, but full expert control whenever desired
- ARM® Multishot technology: 15 HV fault traces are captured per each arc reflection measurement
- ProRange technology: Distance-dependent exponential de-attenuation of more than +22 dB for improved measurement of far-away impedance changes
- Optimised support for all arc reflection methods by Delta-U trigger or Low-High edge trigger
- Two-phase TDR mode and display of up to 6 traces simultaneously, ideal for phase comparison
- Automatic cable end recognition and flagging of fault position
- Compatible with all fault location systems (thumpers)
- Li-Ion battery-operated
- High quality measurement with very fast data rate of more than 400 MHz
- Dedicated internal output impedance compensation not required anymore thanks to sophisticated and advanced signal path design
- Automatic storage of all measurement data and large memory for storing > 100,000 radar measurements
- USB port for export/import data transfer and protocol printing via Reporting Edition software package
- Many different language versions available

OPTIONS

- Separation filter TF-VX (for the operation on live circuits up to 600 V, CAT IV)
- PD pinpointing

ORDERING INFORMATION

Product	Order no.
Teleflex SX-1-VS sales set	1012747
Teleflex SX-1 calibration certificate	90029860
Separation filter TF-VX	1010520

* We reserve the right to make technical changes.

SALES OFFICE

Megger Germany GmbH
Dr.-Herbert-Iann-Str. 6
D-96148 Baunach
T +49 9544 68-0
E team.international@megger.com

TELEFLEX_SX-1_DS_EN_V03

www.megger.com
ISO 9001
The word 'Megger' is a registered trademark

Megger®