

Keysight Technologies

B2200A fA Leakage Switch Mainframe

B2201A 14ch Low Leakage Switch Mainframe

Data Sheet



Introduction

Basic functions

The Keysight Technologies, Inc. B2200A fA leakage switch mainframe and B2201A 14ch low leakage mainframe functions:

- Switches DC current, DC voltage, capacitance and LCR meters
- Set and monitor connection status on front panel
- Configured status display with LED matrix display
- Connection setup by light pen
- Controls through GP-IB interface
- Auto ground function
- Self-test, relay function test
- Relay cleaning

Configuration

Input (B2200A/B2201A)

- IV port: 8 triaxial ports (or 4 Kelvin triaxial ports) low leakage performance
- AUX port: 6 BNC ports dedicated 2 CV ports
- All input ports can use concurrently

Output (B2210A/B2211A)

- 12 triaxial ports per switch module.
- Frame can have 4 modules maximum.
- (Total 48 ports)

Software

The B2200A and B2201A include a CD-ROM with VXI Plug&Play driver which contains capacitance compensation routine.

General specifications		
Temperature range	Operation: Storage:	+5° C to 35° C -20° C to 70° C
Humidity range	Operation: Storage:	+5% to 70% R.H. no condensation (B2200A, B2210A) < 80% @35° C, < 60% @ 65° C no condensation (B2201A, B2211A) < 80% @ 65° C no condensation
Altitude	Operation: Storage:	0 m to 2,000 m 0 m to 15,240 m
Regulatory Compliance	Safety: EMC:	CSA C22.2 No.1010.1/IEC 1010-1 CISPR 11 Group 1 class A&EN50082-1
Power requirement	90 to 264 V (continuous), 47 to 63 Hz, 2 A/200 VA max	
Number of slots	4 slots for 48 mm height switch module.	
Size	B2200A/B2201A B2210A/B2211A 3	430 mm W x 320 mm H x 600 mm D 95 mm W x 48 mm H x 500 mm D
Weight (approx.)	B2200A/B2201A B2210A B2211A	14.0 kg 4.5 kg 3.5 kg
Number of ports (B2210A, B2211A use with B2200A, B2201A)		
	I-V port: AUX port: Output channel:	8 triaxial ports (with guard) 6 BNC ports (2 of CV port) 12 triaxial ports (with guard), max. 48 ports

Switch module specifications (Used with mainframe ¹)		
Condition	B2210A	B2211A
Max current rating (A):	I-V port AUX port	1.0 0.5
Max voltage rating (V):	I-V: (to common) I-V: (to other ch.) AUX: (to common) AUX: (to other ch.)	200 300 100 100
Close channel residual resistance (Ω):	I-V port AUX port	0.6 1.5
Channel isolation resistance (Ω):	I-V port AUX port	1x10 ¹⁴ 1x10 ⁹

Condition: 23° C ± 5° C, 5% to 60% R.H.

¹ B2200A only supports B2210A fA leakage switch module.
B2201A only supports B2211 14ch low leakage switch module.
Mixed configuration is not supported.

Supplemental characteristics (B2200A/B2210A)¹

Offset current	10 fA ²	I-V port
IM noise (RMS)	0.6 fA ³	I-V port
Channel crosstalk capacitance	< 1 pF/ch < 3 pF/ch	I-V port AUX port
Offset voltage	< 50 µV < 80 µV	I-V port AUX port
Settling time ⁴	2.0 sec at 50 fA	
Band width (at -3 dB)	30 MHz	AUX port
Guard capacitance	< 145 pF ⁵	I-V port
Additional C measurement error	< ± 1 % + 0.2 pF ⁶	AUX port

Supplemental characteristics (B2201A/B2211A)¹

Offset current	100 fA ⁷	I-V port
IM Noise (RMS)	5 fA ³	I-V port
Channel crosstalk capacitance	< 0.5 pF/ch < 3 pF/ch	I-V port AUX port
Offset voltage	< 80 µV < 100 µV	I-V port AUX port
Settling time ⁴	2.0 sec at 300 fA	
Band width (at -3 dB)	30 MHz	AUX port
Guard capacitance	< 145 pF ⁵	I-V port
Additional C measurement error	< ± 1 % + 0.2 pF ⁶	AUX port

1. B2200A only supports B2210A fA leakage switch module.
B2201A only supports B2211 14ch low leakage switch module.
Mixed configuration is not supported.
2. The offset current when zero volts is applied to all input and output channels.
This measurement is made on a port, 5 seconds after a switching a relay.
3. Measured 100 PLC by 4156C when zero volts are applied to all other paths.
4. After 10 V applied.
5. The guard capacitance of the closed port on input and output ports when 4 modules per frame are installed.
6. The additional error using the C-compensation algorithm for Keysight 4284 at 1 kHz to 1 MHz, <1000 pF and 3 m cable.
7. The offset current when zero volts is applied to all input and out channels.
This measurement is made on a port, 60 seconds after a switching a relay.

Specification condition

Specification and supplemental characteristics are defined at $23^{\circ}\text{C} \pm 5^{\circ}\text{C} < 60\%$ relative humidity (R.H.)

The supplemental characteristics entries in the following specification are not warranted but they provided useful information about the functions and performances of the instruments.

Accessories & cables

Keysight 16443A	Light pen for B2200A/ B2201A
Keysight 16494A	Triaxial cable
Keysight 16493K	Kelvin triaxial cable (for input port) (Between 4155/56 series or E5270 series and B2200/2201A input port)
Keysight 16494B	Kelvin triaxial cable (for output port)
Keysight 16494F	CMU input cable
Keysight 16493N	GND cable (Between GND of E5270/41501 and B2201A/B2200A)



Keysight B2200A fA leakage switch mainframe (back panel)