


NEW

Liquid Crystal Based Spatial Light Modulator Full High Definition model / SLM-200

Santec spatial light modulator (SLM) is based on reflective liquid crystal on silicon (LCOS) microdisplay technology. The SLMs enable optical phase modulation freely and generate arbitrary 2D phase patterns on a LCOS pixel-by-pixel basis.

SLM-200 series are our latest Full-HD LCOS model. The SLMs are suitable for various scientific and industrial applications, including beam shaping, wavefront correction and optical manipulations.

WUXGA and Full-HD available



Separate model


Features

- ▶ WUXGA (1920 x 1200) and Full-HD (1920 x 1080) available
- ▶ Frame rate, x2 (120Hz)
- ▶ Memory function
- ▶ Triggers-input & output

Applications

- ▶ Beam steering
- ▶ Wavefront correction
- ▶ Pulse/Beam shaping
- ▶ Diffractive optics
- ▶ Optical manipulation
- ▶ Programmable phase pattern

Measurement



All-in-one model

■ Specifications

Item	min	max	Units	Notes
Operating Wavelength range	450	1600	nm	(Refer to appended table about AR coating option)
Panel size	(H)15.42 x (V)9.66		mm	Active area
Pixel resolution	(H)1920 x (V)1200		pixel	
Pixel size / pitch	7.8 / 8.0		μm	
Panel reflectivity	Typ. >80		%	Depending on specified wavelength range
Aperture ratio	95		%	
Gray level	10 (1024)		bit	
Frame rate	60 or 120		Hz	
LCOS drive frequency	1200		Hz	
Phase depth	2π	-	rad.	
Relative phase fluctuation	Typ. <0.001π		rad.	
Response time	Typ. 300		ms	
Signal format	DVI / USB3.0		-	10-bit using RGB 8-bit, 3 colors
Operating temperature range	15	35	degC	
Storage temperature	0	40	degC	
Optical power handling	Typ. 10 ⁻¹		W/cm ²	@1550nm, CW, 2.0mm beam diameter
Dimensions	117.6 x 117.6 x 33.7		mm	
Control software	GUI software for Windows		-	

1) The value is not guaranteed. Please refer santec SLM technical sheet in one instance for judgement of useable light power.

< AR coating option >

Item	Parameter						Units
Ordering code number	-01	-02	-03	-04	-12	-14	-
AR coating range	450-550	750-850	1000-1100	1500-1600	400-800	450-550 / 1500-1600	nm
AR coating reflectance ²⁾	< 0.5				< 1.5	< 0.6	%

2) Angle of incidence = 0 degree

■ Ordering Code

SLM-200-01-XXXX-XX

AR coat range
 00 : non-coating, 01 : 450 ~ 550nm, 02 : 750 ~ 850nm, 03 : 1000 ~ 1100nm, 04 : 1500 ~ 1600nm
 12: 400 ~ 800 nm, 14: 450 ~ 550 nm / 1500~1600 nm CC: custom coating

0001: all-in-one model , 0002: separate model

www.santec.com E-Mail : sales@santec.com

2018 © SANTEC CORPORATION Santec reserves the right to make changes in equipment design, components or specifications without notice.



SANTEC CORPORATION
 5823 Ohkusa-Nenjozaka, Komaki, Aichi 485-0802, Japan Tel. +81-568-79-3536 Fax +81-568-79-1718

SANTEC U.S.A. CORPORATION
 433 Hackensack Ave., Hackensack, NJ 07601, U.S.A. Toll Free +1-800-726-8321(santec-1) Tel. +1-201-488-5505 Fax +1-201-488-7702

SANTEC EUROPE LIMITED
 Grand Union Studios, 332 Ladbrooke Grove, London W10 5AD Tel. +44-20-3176-1550

SANTEC (SHANGHAI) Co., Ltd.
 11F Room E, Hua Du Bldg., No.838 Zhangyang Road, Pudong District, Shanghai 200122 China Tel: +86-21-58361261, +86-21-58361262 Fax: +86-21-58361263