

Manual Supplement

Manual Title: 287/289 Calibration
Part Number: Web-Only
Print Date: February 2008
Revision/Date: 2, 1/19

Supplement Issue: 1
Issue Date: 10/21
Page Count: 1

This supplement contains information necessary to ensure the accuracy of the above manual.

Change #1, 418, a133

In the **AC Voltage Specifications** table on page 6, replace table footnotes [2] and [3] with this text:

[2] Specification increases linearly from -2 % at 200 Hz to -6 % at 440 Hz. Range is limited to 440 Hz.

[3] dBm (600 ohm) is specified by adding +2.2 dB to the dBV range values.

In the **AC Current Specifications** table on page 6, replace table footnotes [2] and [3] with this text:

[2] 10 A to 20 A, 30 seconds on, 10 minutes off. >10 A not specified.

[3] 400 mA continuous; 400 mA to 550 mA for 2 minutes on, 1 minute off.

In the **DC Voltage Specifications** table on page 7, replace table footnotes [2] and [4] with this text:

[2] Specification increases linearly from -2 % at 200 Hz to -6 % at 440 Hz. Range is limited to 440 Hz.

[3] dBm (600 ohm) is specified by adding +2.2 dB to the dBV range values.

In the **DC Current Specifications** table on page 7, replace table footnotes [2] and [4] with this text:

[2] 10 A to 20 A, 30 seconds on, 10 minutes off. >10 A not specified.

[3] 400 mA continuous; 400 mA to 550 mA for 2 minutes on, 1 minute off.

Change #2, a133

On page 27, change the title of Table 8 to:

Table 8. Calibration Adjustment Steps for Firmware Version 1.10 or Higher

Change #3, a133

In Table 7 on page 25 and Table 8 on page 27, change the **Source Value** of steps 3 and 4 to:

Step 3: 0.00 mV / 0 Hz

Step 4: 50.00 mV / 0 Hz