

# Fluke 374 Clamp Meter



Perfect for many current measurement situations

The new Fluke 374 clamp meters offer improved performance perfect for many current measurement situations. With true-rms ac voltage and current measurements, the Fluke 374 can read up to 600 V and 600 A in both ac and dc modes. Additionally, both are compatible with the new iFlex™ flexible current probe (sold separately) which expands the measurement range to 2500 A ac and provides increased display flexibility, ability to measure around awkward sized conductors and improved wire access.



## Specifications

Jaw Opening	1.33" (34mm)
Max Wire Size	750 MCM
Current Range AC (RMS)	0 - 600 A
Accuracy AC Current (50/60Hz)	2% +/- 5 counts
AC Response	True-rms
Current Range DC	0 - 600 A
Accuracy DC current	2% +/- 5 counts
Voltage Range AC	0 - 600 V
Accuracy AC Voltage	1.5% +/- 5 counts
Voltage Range DC	0 - 600 V
Accuracy DC Voltage	1% +/- 5 counts
Resistance Range	0 - 6000 Ω
Mechanical, Environmental and Safety Ratings (Category Ratings)	600 V CAT IV 1000 V CAT III

### iFlex™ i2500-18



Additional accessory for Fluke 374  
2500 Amp AC current measurement with  
iFlex™ flexible current probe (sold separately)