

5000-5500MHz/20Watt/Module

Model Number: KN5250M43A

The model KN5250M43A is a multi-octave high power amplifier operating between 5.0 GHz and 5.5GHz and offering a wide dynamic Range with 20 Watts typical saturated power. The employment of gallium arsenide (GaAs) and chip-and-wire technology in manufacturing ensures this module state-of-the-art power performance with excellent power-to-volume ratio. It is ideal for jamming, EMC, test and measurement applications.

FEATURES:

- Small Size and light weight;
- Instantaneous ultra-broadband;
- 50 Ohms input and Output matched;
- Built-in control and protection circuits.

ELECTRICAL SPECIFICATIONS @ +28.0VDC, 25°C, 50Ω

Parameter	Symbol	Minimum	Typical	Maximum	Units
Operating Frequency	BW	5000		5500	MHz
RF Output Power@P1dB	P ₁	20			Watt
Power Gain	G		43		dB
Small Gain Flatness	Δ G		±2		dB
Input Return Loss	S ₁₁			-10	dB
Harmonics @10W	H		-15		dBc
Spurious Signals	Spur		-55		dBc
In/Output Impedance			50		Ω
Operating Voltage	V _{DC}	24	28	32	Volt
DC Current @20W	I _{DD}		5		Amp
Switching Time@10kHz TTL	Ton/Toff		2	5	Us

MECHANICAL SPECIFICATIONS

Parameter	Value	Units	Limits
Dimensions	180x150x25 [7x5.9x1]	mm [inch]	Maximum
Weight	1.5 [3.3]	kg [lbs]	Maximum
RF Connectors Input	SMA, Female		
RF Connectors Output	SMA, Female		
DC Interface Connector	D-Sub 9-Pin, Male		
Cooling	External Heatsink (Not Supplied)		

ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-20		60	°C	
Non-operating Temperature	-25		65	°C	Storage
Relative Humidity (non-condensing)			95	%	

Absolute Maximum Rating

Input RF drive level without	+5 dBm	Maximum
Load VSWR @ POUT =10W	∞ @ all load phase & amplitude for duration of 30 minute; 3:1 @ all load phase & amplitude continuous	
Thermal Overload	85°C shutdown	Maximum

Focus on Your Application

Chengdu KeyLink Microwave Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761*8708

>> Fax: +86(28)87883266

>> sales@keylinkmw.com

>> www.keylinkmw.com

without notice

Specifications subject to change


5000-5500MHz/20Watt/Module

Model Number: KN5250M43A

DC INTERFACE CONNECTOR

Pin #	Description	Specifications
A1	VDD	28V _{DC}
A2	GND	Ground
1	ENABLE	Amplifier Disable: TTL Logic High (3.3V) (Internally Pulled-Low)
2	NC	No electrical connection
3	NC	No electrical connection
4	GND	Ground
5	NC	No electrical connection

OUTLINE DRAWING (All dimensions in mm [inch])



Focus on Your Application

Chengdu KeyLink Microwave Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761*8708 >> Fax: +86(28)87883266

>> sales@keylinkmw.com >> www.keylinkmw.com

without notice


Specifications subject to change

5000-5500MHz/20Watt/Module


Model Number: KN5250M43A

TYPICAL PERFORMANCE PLOTS (FOR REFERENCE)

Graph 1: Output Power (Low temp. $-20\pm 3^{\circ}\text{C}$)



Graph 2: Output Power (High temp. $+60\pm 3^{\circ}\text{C}$)



Focus on Your Application

Chengdu KeyLink Microwave Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761*8708

>> Fax: +86(28)87883266

>> sales@keylinkmw.com

>> www.keylinkmw.com


without notice

Specifications subject to change


5000-5500MHz/20Watt/Module

Model Number: KN5250M43A

Graph 3: Output Power (Normal temp. +25±3°C)



Power Gain:



Focus on Your Application

Chengdu KeyLink Microwave Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761*8708

>> Fax: +86(28)87883266

>> sales@keylinkmw.com

>> www.keylinkmw.com


without notice

Specifications subject to change

5000-5500MHz/20Watt/Module

Model Number: KN5250M43A

Input Return Loss:



Note:

- 1. Adequate heatsink required.

Focus on Your Application

Chengdu KeyLink Microwave Technology Co., Ltd.

>> 5-2, Huidu Headquarters Park, High-Tech(West) Zone, Chengdu, 611731, P. R. China

>> Phone: +86(28)87870761*8708

>> Fax: +86(28)87883266

>> sales@keylinkmw.com

>> www.keylinkmw.com

without notice

Specifications subject to change