

QCI2619C

High Power, High Isolation

Features:

- * High Power
- * High Isolation
- * Low Insertion Loss
- * Low VSWR

Applications:


- * Wireless
- * Radar
- * Laboratory Test

Description

QCI2619C series Coaxial Isolators cover frequency range 8~12GHz. High power, high isolation and low insertion loss make it ideal for a lot of applications like amplifiers, transceivers, etc.

Specifications

Frequency (MHz)	Bandwidth (MHz)	IL (dB Max.)	Isolation (dB Min.)	VSWR (Max.)	Fwd Power (W Max.)	Rev Power (W)	Connector	Temperature (°C)
8000~12000	4000	0.80	35.0	1.30	30	10	SMA	-10~+60

Outline Drawings


Unit: mm [inch] Tolerance: $\pm 0.2\text{mm}$ [$\pm 0.008\text{in}$]

Mechanical

Size^{*1}: 26*19*12.7mm
1.024*0.748*0.5in

Mounting: 4-M2, depth 5mm

[1] Exclude connectors and terminations.

Connector Naming Rules:

S - SMA Female

Direction Naming Rules:

- 1 - Clockwise
- 2 - Anticlockwise

How To Order
QCI2619C-U-V-W-X-Y-Z

U: Start frequency in MHz

V: Stop frequency in MHz

W: Forward power in W

X: Reverse power in W

Y: Connector type

Z: Direction type

Examples:

To order a QCI2619C series Isolator, 8~12GHz, Forward power 30W, Reverse power 10W, SMA female, Clockwise, specify QCI2619C-8000-12000-30-10-S-1.

Customization is available upon request.