

2-18GHz Broadband Amplifier, +33dBm

2021-11-

Bench-Top Test Equipment



Product Overview

AT-BTHPA-0218-3033GNY is high gain power amplifier with +33dBm output power in the frequency of 2-18GHz. The AC power requirement is +90 to 240V. The module is with SMA connector.

The power amplifier has high gain, high linearity, low input/output return loss and flat gain response.

More information, please visit www.atmicrowave.com

Advantages

- ✓ Frequency: 2-18GHz
- ✓ Pout:+33dBm
- ✓ Small signal gain: 30dB
- ✓ Single Power Supply

Application

- ✓ 5G Communication
- ✓ Test Equipment
- ✓ ROF (RF Over Fiber)
- ✓ Radar System

Key Features

Parameter	Min	Typical	Max
Frequency		2-18GHz	
Gain	27	30dB	
Gain Flatness		+/-2.5dB	
P1dB		+30dBm	
Psat	+32dBm	+33dBm	
Power Supply	+90V	+220V	+240V
Power Consumption		50W	
Input Return Loss		-10dB	
Output Return Loss		-5dB	
Spec Temp		25C	





AT-BTHPA-0218-3033GNY

2-18GHz Power Amplifier

Mechanical Information

Item	Description
Input Port	SMA Female
Output Port	SMA Female
Case Material	Aluminum
Finish	Painting
Weight	1.6KG
Size:	See outline

Absolute Maximum Ratings Table

Parameter	Value
Drain Supply	+260V
RF Input Power	+10 dBm
Operating Temperature	-20 to +70C
Storage Temperature	-65 to +150C

Notes:

1. Datasheet may be changed according to update of MMIC, Raw materials , process, and so on.
2. This data is only for reference, not for guaranteed specifications.
3. Please contact AT Microwave team to make sure you have the most current data.





AT-BTHPA-0218-3033GNY

2-18GHz Power Amplifier

Dimension: (unit in mm)

