

# 100MHz-8GHz Low Noise Amplifier



### Product Overview

AT-LNA-0008-3302A is high gain low noise amplifier with 33dB gain in the frequency of 100MHz-8GHz. The DC power requirement is +5/160mA. The module is with SMA connector.

AT Microwave can provide all kinds of coaxial low noise amplifiers, with frequency from 0.01-67GHz, gain from 20 to 60dB, Pout from +5 to +27dBm, and connectors from SMA to 1.85mm.

More information, please visit [www.atmicrowave.com](http://www.atmicrowave.com)

### Advantages

- ✓ Frequency: 100MHz-8GHz
- ✓ Small signal gain: 33dB
- ✓ NF=2dB
- ✓ Single Power Supply

### Application

- ✓ 5G Communication
- ✓ Test Equipment
- ✓ ROF (RF Over Fiber)
- ✓ Radar System

### Key Features

Parameter	Min	Typical	Max
Frequency		100MHz-8GHz	
Gain (0.1-6GHz)	30dB	33 dB	
NF		2	4
P1dB		+16dBm	
Psat		+18dBm	
Drain Supply		+5V	+8V
Current		160 mA	200mA
Input Return Loss		-8dB	
Output Return Loss		-10dB	
Spec Temp		25C	





# AT-LNA-0008-3302A

100MHz-8GHz Low Noise Amplifier

## Mechanical Information

Item	Description
Input Port	SMA Female
Output Port	SMA Female
Case Material	Copper
Finish	Gold Plated
Weight	55g
Size:	See outline

## Absolute Maximum Ratings Table

Parameter	Value
Drain Supply	+13V
RF Input Power	+10 dBm
Operating Temperature(note)	-20 to + 70C
Storage Temperature	-65 to +150C

Note: -40 to +85C is available according to request.

### Caution:


Please pay attention to the case temperature. If case temperature exceed higher than +50C, heat sink and fan are required, or the amplifier may be damaged.

## Notes:


1. Datasheet may be changed according to update of MMIC, Raw materials , process, and so on.
2. This data is only for reference, not for guaranteed specifications.
3. Please contact AT Microwave team to make sure you have the most current data.



### Test Data




Gain vs Frequency




Return Loss vs Frequency






P3db vs Frequency



NF vs Frequency



**Dimension:** (unit in mm)



	<26.5GHz	<40GHz	<50GHz	<67GHz
Connector	SMA	2.92mm	2.4mm	1.85mm
Lenth of a	9.4mm	9.5mm	10.8mm	11.3mm

Note: Female Default. Contact with us for other types.

