

### Broadband Wilkinson Power Divider 10-26.5GHz, SMA Female

2022-7-11



#### Product Overview

AT Microwave offers high performance and broadband power divider from DC-67GHz, with SMA, 2.92mm, 2.4mm and 1.85mm connectors.

Based on our excellent design work, precise machine tolerance and outstanding quality plating, we can provide band pass filter with low insertion loss, good return loss and high rejection at the same time.

More information, please visit [www.atmicrowave.com](http://www.atmicrowave.com)

#### Advantages

- ✓ Broadband Performance
- ✓ Low Insertion Loss
- ✓ Good Amplitude and Phase balance
- ✓ Good Return Loss


#### Application

- ✓ 5G Communication
- ✓ Test Equipment
- ✓ ROF (RF Over Fiber)
- ✓ Radar System

#### Key Features

Parameter	Min	Typical	Max
Frequency Range		10-26.5GHz	
Normal Power Splitting		3 dB	
Normal Phase Shift		0 Degree	
Extra Insertion Loss		-0.5dB	-1.0dB
Amplitude Balance		+/-0.4dB	+/-1.2dB
Phase Balance		+/-2 Degree	+/-5 Degree
VSWR		1.5	1.8
Isolation	18dB	20dB	
CW Power			20W Forward 1W Reverse
Peak Power			200W
Spec Temp		25C	





# AT-PD2-1026

10-26.5GHz Broadband Wilkinson Power Divider

## Mechanical Information

Item	Description
Input Port	SMA Female
Output Port	SMA Female
Case Material	Aluminum
Finish	Painted
Weight	80g
Size:	See outline

## Absolute Maximum Ratings Table

Parameter	Value
RF Input Power CW	20W Forward; 1W Reverse
Operating Temperature(note)	-40 to + 85C
Storage Temperature	-65 to +125C

## Notes:

1. Datasheet may be changed according to update of MMIC, Raw materials , process, and so on.
2. This data is only for reference, not for guaranteed specifications.
3. Please contact AT Microwave team to make sure you have the most current data.



### Dimension: (unit in mm)

