




LB-1500-10-C-7/16F Standard Gain Horn Antenna 0.49-0.75GHz 10dB Gain 7/16(DIN) Female

Standard Gain Horn Antenna Operating From 0.49GHz to 0.75GHz With a Nominal 10dB Gain With 7/16(DIN) Female Connector

Product Information

SKU	LB-1500-10-C-7/16F
-----	--------------------

Description

Standard Gain Horn Antenna LB-1500-10-C-7/16F, operating from 0.49 to 0.75GHz with a nominal 10dB gain and low VSWR 1.25:1 with 7/16(DIN) Female connector output. The model LB-1500-10-C-7/16F has uniform gain through its frequency span, providing efficient performance characteristics and directionality. It can handle 800W continuously and 3000W peak power. Constructed of lightweight corrosion-resistant aluminum, the antenna will provide years of trouble-free indoor and outdoor service. This standard gain horn antenna is linearly polarized and ideally suited for EMI testing, direction finding, surveillance, antenna gain and pattern measurements and other applications.

Technical Specification


Electrical Specification		Interface	
Frequency, Min (GHz)	0.49	Output Type	Coaxial
Frequency, Max (GHz)	0.75	Flange Type	Cover
Waveguide Type	Rectangular	Connector	7/16 DIN
Waveguide Size EIA WR	WR1500	Connector Gender	Female
Gain, Typ (dBi)	10	Mechanical Specification	
Polarization	Linear	Figure	C Type
3dB Beamwidth, E-Plane, Typ (Deg.)	50	Body Material	Al
3dB Beamwidth, H-Plane, Typ (Deg.)	46	Finish	Chemical Conversion Coating, Gray Paint
Cross Pol. Isolation, Typ (dB)	30	Size, W (mm)	698
VSWR, Typ	1.25:1	Size, H (mm)	504
Impedance, (Ohm)	50	Size, L (mm)	1025
Power Handling, CW, (W)	800	Weight, (kg)	21
Power Handling, Peak, (W)	3000		

Additional Information


Application	General Purpose Indoor & Outdoor, Fixed	Solution for	Gain Reference Antenna Measurement Reflector Feed Far-field Measurement System Intergration Material Measurement
-------------	---	--------------	---

Outline Drawing


7/16(DIN) Female Output (P/N: LB-1500-10-C-7/16F)



7/16(DIN) Female Output with Round Mounting Bracket (Option, P/N: LB-1500-10-C-MB)




7/16(DIN) Female Output with L Type Mounting Bracket (Option, P/N: LB-1500-10-C-L)




Typical Test Results

Gain




Antenna Factor





Antenna Factor (Table)


Frequency (GHz)	Gain (dBi)	Antenna Factor (dB/m)	Frequency (GHz)	Gain (dBi)	Antenna Factor (dB/m)
0.49	9.81	14.20	0.63	11.91	14.29
0.50	9.95	14.24	0.64	12.10	14.24
0.51	10.09	14.27	0.65	12.29	14.18
0.52	10.23	14.30	0.66	12.48	14.12
0.53	10.38	14.32	0.67	12.67	14.06
0.54	10.52	14.33	0.68	12.85	14.01
0.55	10.67	14.35	0.69	13.01	13.97
0.56	10.82	14.36	0.70	13.15	13.96
0.57	10.97	14.36	0.71	13.27	13.97
0.58	11.12	14.36	0.72	13.36	13.99
0.59	11.27	14.35	0.73	13.45	14.02
0.60	11.43	14.34	0.74	13.55	14.05
0.61	11.59	14.32	0.75	13.65	14.06
0.62	11.76	14.29			

VSWR



Pattern





Related Products



LB-1500-10-C-MB Round Type Mounting Bracket



LB-1500-10-C-L L type mounting bracket




Carrying Case_LB-1500-10-C Alloy Carrying Case

Similar Products




LB-1500-10-A Standard Gain Horn Antenna 0.49-0.75GHz 10dB Gain Rectangular Waveguide Interface




LB-1500-10-ASPO Standard Gain Horn Antenna 0.49-0.75GHz 10dB Gain Rectangular Waveguide Interface




LB-1500-10-C-NF Standard Gain Horn Antenna 0.49-0.75GHz 10dB Gain N Type Female




LB-1500-10-C-NFSPO Standard Gain Horn Antenna 0.49-0.75GHz 10dB Gain N Type Female



LB-1500-10-C-SF Standard Gain
Horn Antenna 0.49-0.75GHz 10dB
Gain SMA Female



LB-1500-10-C-SFSPO Standard
Gain Horn Antenna 0.49-0.75GHz
10dB Gain SMA Female



LB-1500-10-C-7/16FSPO
Standard Gain Horn Antenna
0.49-0.75GHz 10dB Gain
7/16(DIN) Female

About this Datasheet

• Product Information Product Link: https://www.ainfoinc.com/lb-1500-10-c-7-16f-standard-gain-horn-antenna-0-49-0-75-ghz-10db-gain-7-16-din-female Data subject to change without notice. © A-INFO INC. 2023. All Rights Reserved	• Contact Us Address:dd 60 Tesla, Irvine, CA 92618, USA Website: www.ainfoinc.com Email: sales@ainfoinc.com	• Phone & Fax Phone: +1-949-639-9688 +1-949-639-9608 Fax: +1-949-639-9670
---	--	---