


For reference only. See data sheet for the detailed specifications.


Technical Specification



Frequency Range(GHz)	7.05 - 10.0
Waveguide	WR112
Gain(dBi)	20 Typ.
Polarization	Linear
3dB Beamwidth(deg)	E Plane: 15 Typ.
	H Plane: 15 Typ.
Side Lobe Level(dB)	E Plane: 35 Min.
	H Plane: 35 Min.
Cross Pol. Isolation(dB)	35 Typ.
VSWR	A Type: 1.20:1 Max.
	C Type: 1.50:1 Max.
Output	A Type: FBP84(UBR84)
	C Type: N-Female or SMA-Female or TNC-Female or 7mm or 3.5mm-Female
Material	Al
Finish	Chemical Conversion Coating, Gray Paint
Size(mm)	A Type: 224.9 x 224.9 x 397
	C Type: 224.9 x 224.9 x 437
Net Weight(Kg)	A Type: 0.88 Around
	C Type: 0.95 Around


Outline Drawing (Size: mm)

FBP84 Output (P/N: LB-DG-112-20-A)



N-Female Output (P/N: LB-DG-112-20-C-NF)

For SMA-Female, TNC-Female, 7mm or 3.5mm-Female output outline drawing, please contact A-INFO.



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608


Page 2 of 9

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

N-Female Output with Round Mounting Bracket (Option, P/N: LB-DG-112-20-MB)

For SMA-Female, TNC-Female, 7mm or 3.5mm-Female output outline drawing, please contact A-INFO.





Flange Drawing (Size: mm)




FBP84

Test Results


1. Gain & Antenna Factor




2. Cross Polarization Isolation



3. VSWR(C Type)



4. Pattern



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Page 7 of 9

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

