

QPDO-E-100-10.1

External Reference, 100MHz, 10.1GHz

Features:

- * High Frequency Stability
- * Ultra Low Phase Noise


Applications:

- * Wireless
- * Transceiver
- * Laboratory Test
- * Radar

Electrical

Output Frequency:	10.1GHz
Output Power:	13dBm min
Spurious:	-70dBc max.
Harmonic:	-20dBc max.
External Reference:	100MHz
	-130dBc/Hz@100Hz
	-155dBc/Hz@1KHz
	-165dBc/Hz@10KHz
	-165dBc/Hz@100KHz
	-165dBc/Hz@1MHz
Input Power:	3~10dBm
Phase Noise:	-88dBc/Hz@100Hz
	-113dBc/Hz@1KHz
	-120dBc/Hz@10KHz
	-120dBc/Hz@100KHz
	-140dBc/Hz@1MHz
Voltage:	+12V DC
Current:	300mA max.
Lock Indicator (LI):	TTL logic
	High: locked
	Low: unlocked

Outline Drawings



Unit: mm [in]

Tolerance: $\pm 0.2\text{mm}$ [$\pm 0.008\text{in}$]

How To Order

QPDO-E-100-10.1

Customization is available upon request.

Mechanical

Size*1:	50.8*47.8*15.7mm
	2*1.882*0.618in
RF Connectors:	SMA Female
Power Supply Interface:	Feed Through
Mounting:	4-M2, Depth 5mm

[1] Exclude connectors.

Environmental

Operating Temperature:	-40~+70°C
Non-operating Temperature:	-55~+85°C