



For reference only. See data sheet for the detailed specifications.

Technical Specification



EIA WR	WR34
Frequency Range(GHz)	24.0 – 27.0
Insertion Loss(dB)	0.4 Max.
Isolation(dB)	20 Min.
VSWR	1.25:1 Max.
Power Handling(W CW)	50
Flange	FBP260(UBR260) (Modified with 4xM3 Deep 4 threaded holes)
Material	Al
Size(mm)	30 x 30 x 21.1
Net Weight(Kg)	0.05 Around

Outline Drawing (Size: mm)



AINFO Inc.


Page 1 of 4

China(Beijing): Tel: (+86) 10-6266-7326,
China(Chengdu): Tel: (+86) 28-8519-2786,
USA: Tel: (+1) 949-639-9688,

(+86) 10-6266-7327 Fax: (+86) 10-6266-7379
(+86) 28-8519-3044 Fax: (+86) 28-8519-3068
(+1) 949-639-9608 Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Flange Outline Drawing (Size: mm)



FBP260

AINFO Inc.

Page 2 of 4


China(Beijing): Tel: (+86) 10-6266-7326,
China(Chengdu): Tel: (+86) 28-8519-2786,
USA: Tel: (+1) 949-639-9688,

(+86) 10-6266-7327 Fax: (+86) 10-6266-7379
(+86) 28-8519-3044 Fax: (+86) 28-8519-3068
(+1) 949-639-9608 Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results

Port1-Port2: I.L., Isolation & VSWR



Port2-Port3: I.L., Isolation & VSWR



Port3-Port1: I.L., Isolation & VSWR

