




For reference only. See data sheet for the detailed specifications.

Technical Specification



EIA WR	WR34
Frequency Range(GHz)	22.0 – 33.0
Coupling(dB)	20
Coupling Accuracy(dB)	±1.0 Max.
Frequency Sensitivity(dB)	±0.9 Max.
Directivity(dB)	30 Min.
Insertion Loss(dB)	0.6 Max. (Not including the theoretical loss 0.09dB)
Mainline VSWR	1.10:1 Max.
Secondline VSWR	1.15:1 Max.
Flange	FBP260(UBR260)
Material	Cu
Size(mm)	228.6 x 21.1 x 63.5
Net Weight(Kg)	0.64 Around

Outline Drawing (Size: mm)



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,


(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Page 1 of 6

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Flange Drawing (Size: mm)




FBP260


Test Results

Coupling


Port 1




Port 2




Directivity Port 1




Port 2



I.L. (Including the theoretical loss 0.09dB)




Mainline VSWR




Secondline VSWR

Port 1



Port 2



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com