



For reference only. See data sheet for the detailed specifications.

Technical Specification



EIA WR	WR34
Frequency Range(GHz)	22.0 - 33.0
Band Width	FULL
Insertion Loss(dB)	0.2 Max. (Not including the theoretical loss 3.0dB)
VSWR	1.50:1 Typ.
Amplitude Balance(dB)	±0.3 Max.
Phase Balance(°)	±5 Max.
Flange	FBP260(UBR260) (Modified with 4xM3 deep 3)
Material	Cu
Size(mm)	29.21 x 29.21 x 25.16
Net Weight(Kg)	0.16 Around

Outline Drawing (Size: mm)



AINFO Inc.

China(Beijing):
China(Chengdu):
USA :

Tel: (+86) 10-6266-7326,
Tel: (+86) 28-8519-2786,
Tel: (+1) 949-639-9688,


(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608

Page 1 of 4

Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com


Flange Drawing (Size: mm)




FBP260

Test Results

1. Insertion Loss(Including the theoretical loss 3.0dB)



2. VSWR



3. Amplitude Balance & Phase Balance

