


For reference only. See data sheet for the detailed specifications.

Technical Specification




EIA WR	WR75
Switch Type	DPDT Latching
Frequency Range(GHz)	10.0 – 15.0
DC Power Supply(V)	27 ± 3
Current(A)	1.0 Max.
VSWR	1.10:1 Max.
Isolation(dB)	60 Min.
Insertion Loss(dB)	0.1 Max.
Switching Speed(ms)	110 Max.
Power Handling(W CW)	800 Max.
Peak Power(KW)	250
Flange	FBP120(UBR120) (Modified with 4x M4 deep 5)
Operating Temperature(°C)	-55 ~ +85
Material	Al
Finish	Chemical Conversion Coating, Black Paint
Size(mm)	57.15 x 70.4 x 147.1
Net Weight(Kg)	0.83 Around

Outline Drawing (Size: mm)




Outline Drawing (Size: mm)




FBP120

Test Results


I.L. (From port 1 to port 2) @Pos. 1




I.L. (From port 3 to port 4) @Pos. 1




Iso. (From port 1 to port 3) @ Pos. 1




Iso. (From port 1 to port 4) @ Pos. 1




Iso. (From port 2 to port 4) @ Pos. 1




Iso. (From port 3 to port 2) @ Pos. 1




I.L. (From port 1 to port 3) @ Pos. 2




I.L. (From port 2 to port 4) @ Pos. 2




Iso. (From port 1 to port 2) @ Pos. 2



Iso. (From port 2 to port 3) @ Pos. 2



Iso. (From port 3 to port 4) @ Pos. 2



Iso. (From port 4 to port 1) @ Pos. 2

