

Technical Specification

P/N:DS-50600	
Frequency Range(GHz)	0.5 - 6.0
Gain(dBi)	7 Typ.
Polarization	Linear
3dB Beamwidth(deg)	E Plane: 68 - 44
	H Plane: 131 - 60
VSWR	2.0:1 Typ. / 3.0:1 Max.
Output	N-Female
Average Power(W CW)	300 (80 @ 6.0GHz)
Peak Power(KW)	3
Material	Al
Size(mm)	355 x 78.1 x 494.8
Net Weight(Kg)	0.70 Around

P/N:DS-50600C	
Frequency Range(GHz)	0.5 - 6.0
Gain(dBi)	7 Typ.
Polarization	Linear
3dB Beamwidth(deg)	E Plane: 68 - 44
	H Plane: 131 - 60
VSWR	2.0:1 Typ. / 3.0:1 Max.
Output	N-Female
Average Power(W CW)	300 (80 @ 6.0GHz)
Peak Power(KW)	3
Material	Al
Size(mm)	355 x 120 x 487.1
Net Weight(Kg)	0.84 Around

P/N:DS-50600E	
Frequency Range(GHz)	0.5 - 6.0
Gain(dBi)	7 Typ.
Polarization	Linear
3dB Beamwidth(deg)	E Plane: 68 - 44
	H Plane: 131 - 60
VSWR	2.0:1 Typ. / 3.0:1 Max.
Output	N-Female
Average Power(W CW)	300 (80 @ 6.0GHz)
Peak Power(KW)	3
Material	Al
Size(mm)	355 x 79 x 688.5
Net Weight(Kg)	1.25 Around

AINFO Inc.

Page 1 of 8




China(Beijing): Tel: (+86) 10-6266-7326,
China(Chengdu): Tel: (+86) 28-8519-2786,
USA: Tel: (+1) 949-639-9688,

(+86) 10-6266-7327 Fax: (+86) 10-6266-7379
(+86) 28-8519-3044 Fax: (+86) 28-8519-3068
(+1) 949-639-9608 Fax: (+1) 949-639-9670





Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Outline Drawing (Size: mm)

DS-50600 (P/N: DS-50600)



DS-50600 with Mounting Bracket (Option, P/N: DS-50600-MB)



AINFO Inc.

Page 2 of 8


China(Beijing): Tel: (+86) 10-6266-7326,
China(Chengdu): Tel: (+86) 28-8519-2786,
USA: Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608


Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670

Website: www.ainfoinc.com
Email: sales@ainfoinc.com




DS-50600 with Mounting Bracket for Tripod Application (Option, P/N: DS-50600-MBA)



DS-50600C (P/N: DS-50600C)



DS-50600E (P/N: DS-50600E)



AINFO Inc.

Page 4 of 8


China(Beijing): Tel: (+86) 10-6266-7326,
China(Chengdu): Tel: (+86) 28-8519-2786,
USA: Tel: (+1) 949-639-9688,

(+86) 10-6266-7327
(+86) 28-8519-3044
(+1) 949-639-9608
Fax: (+86) 10-6266-7379
Fax: (+86) 28-8519-3068
Fax: (+1) 949-639-9670


Website: www.ainfoinc.com
Email: sales@ainfoinc.com

Test Results


1. Gain



2. Antenna Factor



3. VSWR



4. Pattern

