


LB-19-25-C-2.4F Standard Gain Horn Antenna 40-50GHz 25dB Gain 2.4mm Female

Standard Gain Horn Antenna Operating From 40GHz to 50GHz With a Nominal 25dB Gain With 2.4mm Female Connector



Product Information

SKU	LB-19-25-C-2.4F
-----	-----------------

Description

Standard Gain Horn Antenna LB-19-25-C-2.4F, operating from 40 to 50GHz with a nominal 25dB gain and low VSWR 1.25:1 with 2.4mm Female connector output. The model LB-19-25-C-2.4F has uniform gain through its frequency span, providing efficient performance characteristics and directionality. It can handle 10W continuously and 20W peak power. Constructed of lightweight corrosion-resistant aluminum, the antenna will provide years of trouble-free indoor and outdoor service. This standard gain horn antenna is linearly polarized and ideally suited for EMI testing, direction finding, surveillance, antenna gain and pattern measurements and other applications.

Technical Specification


Electrical Specification		Interface	
Frequency, Min (GHz)	40	Output Type	Coaxial
Frequency, Max (GHz)	50	Connector	2.4mm
Waveguide Type	Rectangular	Connector Gender	Female
Waveguide Size EIA WR	WR19	Mechanical Specification	
Gain, Typ (dBi)	25	Figure	C Type
Polarization	Linear	Body Material	Cu
3dB Beamwidth, E-Plane, Typ (Deg.)	9	Finish	Gold Plated and Silver Plated, Gray Paint
3dB Beamwidth, H-Plane, Typ (Deg.)	11	Size, W (mm)	49
Cross Pol. Isolation, Typ (dB)	45	Size, H (mm)	41
VSWR, Typ	1.25:1	Size, L (mm)	156
Impedance, (Ohm)	50	Weight, (kg)	0.2
Power Handling, CW, (W)	10		
Power Handling, Peak, (W)	20		

Additional Information


Application	General Purpose Indoor & Outdoor, Fixed	Solution for	Gain Reference Antenna Measurement Reflector Feed Far-field Measurement System Intergration Material Measurement
-------------	---	--------------	---

Outline Drawing


2.4mm-Female Output (P/N: LB-19-25-C-2.4F)



2.4mm-Female Output with Round Mounting Bracket (Option, P/N: LB-19-10-C-MB)




2.4mm-Female Output with L Type Mounting Bracket (Option, P/N: LB-19-10-C-MBL)




Typical Test Results

Gain




Antenna Factor




Antenna Factor (Table)

Frequency(GHz)	Gain(dB)	Antenna Factor(dB/m)
40	23.64	38.61
40.5	23.65	38.71
41	23.76	38.71
41.5	23.62	38.95
42	23.79	38.88
42.5	23.96	38.82
43	24.02	38.86
43.5	24.18	38.80
44	24.07	39.00
44.5	24.23	38.95
45	24.24	39.04
45.5	24.30	39.07
46	24.38	39.08
46.5	24.22	39.34
47	24.28	39.37
47.5	24.28	39.47
48	24.49	39.34
48.5	24.62	39.31
49	24.45	39.57
49.5	24.52	39.58
50	24.54	39.65





Cross Polarization Isolation















VSWR















Pattern






























Related Products



LB-19-10-C-MB Round Type Mounting Bracket



LB-19-10-C-MBL L type mounting bracket



LB-19-10-C-MA Stinger Type Mounting Bracket



Tripod_15Kg Al Alloy Tripod



3033HL Wooden Tripod



3033QM Wooden Tripod Metalfree



Carrying Case_LB-19-25-C Al Alloy Carrying Case



HSCS_4-40UNC_Pack Assembly Pack



2.4M-2.4M-B020-500 Flexible Cable Assembly 500mm DC-50GHz 2.4mm Male to 2.4mm Male



2.4M-2.4M-B020-1000 Flexible Cable Assembly 1000mm DC-50GHz 2.4mm Male to 2.4mm Male



2.4M-2.4M-B020-1500 Flexible Cable Assembly 1500mm DC-50GHz 2.4mm Male to 2.4mm Male



2.4M-2.4M-B020-2000 Flexible Cable Assembly 2000mm DC-50GHz 2.4mm Male to 2.4mm Male



2.4M-2.4M-B020-3000 Flexible Cable Assembly 3000mm DC-50GHz 2.4mm Male to 2.4mm Male



2.4M-2.4M-B020-5000 Flexible Cable Assembly 5000mm DC-50GHz 2.4mm Male to 2.4mm Male



2.4M-2.4M-B020-10000 Flexible Cable Assembly 10000mm DC-50GHz 2.4mm Male to 2.4mm Male



2.4M-2.4F-B020S-500 Flexible Cable Assembly 500mm DC-50GHz 2.4mm Male to 2.4mm Female



2.4M-2.4F-B020S-1000 Flexible Cable Assembly 1000mm DC-50GHz 2.4mm Male to 2.4mm Female



2.4M-2.4F-B020S-1500 Flexible Cable Assembly 1500mm DC-50GHz 2.4mm Male to 2.4mm Female



2.4M-2.4F-B020S-2000 Flexible Cable Assembly 2000mm DC-50GHz 2.4mm Male to 2.4mm Female



2.4M-2.4F-B020S-3000 Flexible Cable Assembly 3000mm DC-50GHz 2.4mm Male to 2.4mm Female



2.4M-2.4F-B020S-5000 Flexible Cable Assembly 5000mm DC-50GHz 2.4mm Male to 2.4mm Female




2.4M-2.4F-B020S-10000 Flexible Cable Assembly 10000mm DC-50GHz 2.4mm Male to 2.4mm Female

Similar Products



LB-19-25-A Standard Gain Horn Antenna 40-60GHz 25dB Gain Rectangular Waveguide Interface



LB-19-25-ASPO Standard Gain Horn Antenna 40-60GHz 25dB Gain Rectangular Waveguide Interface



LB-19-25-C-2.4FSPO Standard Gain Horn Antenna 40-50GHz 25dB Gain 2.4mm Female



LB-19-25-C-1.85F Standard Gain Horn Antenna 40-60GHz 25dB Gain 1.85mm Female



LB-19-25-C-1.85FSPO Standard
Gain Horn Antenna 40-60GHz
25dB Gain 1.85mm Female

About this Datasheet

● Product Information Product Link: https://www.ainfoinc.com/lb-19-25-c-2-4f-standard-gain-horn-antenna-40-50-ghz-25db-gain-2-4mm-female Data subject to change without notice. © A-INFO INC. 2023. All Rights Reserved	● Contact Us Address: 60 Tesla, Irvine, CA 92618, USA Website: www.ainfoinc.com Email: sales@ainfoinc.com	● Phone & Fax Phone: +1-949-639-9688 +1-949-639-9608 Fax: +1-949-639-9670
---	--	---