




LB-340-10-C-NFSPO Standard Gain Horn Antenna 2.2-3.3GHz 10dB Gain N Type Female

Standard Gain Horn Antenna Operating From 2.2GHz to 3.3GHz With a Nominal 10dB Gain With N Type Female Connector

Product Information

SKU	LB-340-10-C-NFSPO
-----	-------------------

Description

Standard Gain Horn Antenna LB-340-10-C-NFSPO, operating from 2.2 to 3.3GHz with a nominal 10dB gain and low VSWR 1.3:1 with N Type Female connector output. The model LB-340-10-C-NFSPO has uniform gain through its frequency span, providing efficient performance characteristics and directionality. It can handle 300W continuously and 3000W peak power. Constructed of lightweight corrosion-resistant aluminum, the horn comes with a specially designed weatherproof radome which provides excellent protection against the rain and dust but has very little loss across the full operating frequency band. This standard gain horn antenna is linearly polarized and ideally suited for EMI testing, direction finding, surveillance, antenna gain and pattern measurements and other applications.

Technical Specification


Electrical Specification		Interface	
Frequency, Min (GHz)	2.2	Output Type	Coaxial
Frequency, Max (GHz)	3.3	Connector	N Type
Waveguide Type	Rectangular	Connector Gender	Female
Waveguide Size EIA WR	WR340	Mechanical Specification	
Gain, Typ (dBi)	10	Figure	C Type
Polarization	Linear	Body Material	Al
3dB Beamwidth, E-Plane, Typ (Deg.)	46	Finish	Chemical Conversion Coating, Gray Paint
3dB Beamwidth, H-Plane, Typ (Deg.)	42	Size, W (mm)	172
Cross Pol. Isolation, Typ (dB)	25	Size, H (mm)	130
VSWR, Typ	1.30:1	Size, L (mm)	365
Impedance, (Ohm)	50	Weight, (kg)	1.72
Power Handling, CW, (W)	300		
Power Handling, Peak, (W)	3000		

Additional Information


Application	Outdoor, Waterproof and Dustproof, Fixed	Solution for	Gain Reference Antenna Measurement Reflector Feed Far-field Measurement System Intergration Material Measurement
-------------	--	--------------	---

Outline Drawing


N-Female Output with Radome (Option, P/N: LB-340-10-C-NFSPO, Outdoor Application)



N-Female Output with Round Mounting Bracket & Radome (Option, P/N: LB-340-10-C-MB & LB-340-10-C-NFSPO, Outdoor Application)




N-Female Output with L Type Mounting Bracket & Radome (Option, P/N: LB-340-10-C-L & LB-340-10-C-NFSP0, Outdoor Application)




Typical Test Results

Gain




Antenna Factor




Antenna Factor (Table)

Frequency(GHz)	Gain(dBi)	Antenna Factor(dB/m)
2.2	10.27	26.79
2.3	10.69	26.75
2.4	11.03	26.78
2.5	11.44	26.73
2.6	11.78	26.73
2.7	12.14	26.70
2.8	12.56	26.59
2.9	12.92	26.54
3.0	13.24	26.51
3.1	13.58	26.46
3.2	13.85	26.46
3.3	13.94	26.64





Cross Polarization Isolation



VSWR



Pattern



Related Products



LB-340-10-C-MB Round Type Mounting Bracket



LB-340-10-C-L L type mounting bracket



LB-340-10-C-MA Stinger Type Mounting Bracket



Tripod_50Kg Al Alloy Tripod



Carrying Case_LB-340-10-C Al Alloy Carrying Case



NM-NM-A050-1000 Flexible Cable Assembly 1000mm DC-18GHz N Male to N Male



NM-NM-A050-1500 Flexible Cable Assembly 1500mm DC-18GHz N Male to N Male



NM-NM-A050-2000 Flexible Cable Assembly 2000mm DC-18GHz N Male to N Male



NM-NM-A050-3000 Flexible Cable Assembly 3000mm DC-18GHz N Male to N Male



NM-NM-A050-5000 Flexible Cable Assembly 5000mm DC-18GHz N Male to N Male



NM-NM-A050-10000 Flexible Cable Assembly 10000mm DC-18GHz N Male to N Male



NM-NM-A050-20000 Flexible Cable Assembly 20000mm DC-18GHz N Male to N Male



NM-NM-A100-500 Flexible Cable Assembly 500mm DC-18GHz N Male to N Male



NM-NM-A100-1000 Flexible Cable Assembly 1000mm DC-18GHz N Male to N Male



NM-NM-A100-1500 Flexible Cable Assembly 1500mm DC-18GHz N Male to N Male



NM-NM-A100-2000 Flexible Cable Assembly 2000mm DC-18GHz N Male to N Male



NM-NM-A100-3000 Flexible Cable Assembly 3000mm DC-18GHz N Male to N Male



NM-NM-A100-5000 Flexible Cable Assembly 5000mm DC-18GHz N Male to N Male



NM-NM-A100-10000 Flexible Cable Assembly 10000mm DC-18GHz N Male to N Male



NM-NM-A100-20000 Flexible Cable Assembly 20000mm DC-18GHz N Male to N Male

Similar Products



LB-340-10-A Standard Gain Horn Antenna 2.2-3.3GHz 10dB Gain Rectangular Waveguide Interface



LB-340-10-ASPO Standard Gain Horn Antenna 2.2-3.3GHz 10dB Gain Rectangular Waveguide Interface



LB-340-10-C-NF Standard Gain Horn Antenna 2.2-3.3GHz 10dB Gain N Type Female




LB-340-10-C-SF Standard Gain Horn Antenna 2.2-3.3GHz 10dB Gain SMA Female



LB-340-10-C-SFSPO Standard Gain Horn Antenna 2.2-3.3GHz 10dB Gain SMA Female



LB-340-10-C-7/16F Standard Gain Horn Antenna 2.2-3.3GHz 10dB Gain 7/16(DIN) Female



LB-340-10-C-7/16FSP Standard Gain Horn Antenna 2.2-3.3GHz 10dB Gain 7/16(DIN) Female

About this Datasheet

• Product Information

Product Link:
<https://www.ainfoinc.com/lb-340-10-c-nfspo-standard-gain-horn-antenna-2-2-3-3-ghz-10db-gain-n-type-female>
 Data subject to change without notice.
 © A-INFO INC. 2023. All Rights Reserved

• Contact Us

Address:dd
 60 Tesla, Irvine, CA 92618,
 USA

Website:
www.ainfoinc.com

Email:
sales@ainfoinc.com

• Phone & Fax

Phone:
 +1-949-639-9688
 +1-949-639-9608

Fax:
 +1-949-639-9670