


LB-51-25-ASPO Standard Gain Horn Antenna 15-22GHz 25dB Gain Rectangular Waveguide Interface



Standard Gain Horn Antenna Operating From 15GHz to 22GHz With a Nominal 25dB Gain With Rectangular Waveguide Interface

Product Information

SKU	LB-51-25-ASPO
-----	---------------

Description

Standard Gain Horn Antenna LB-51-25-ASPO, operating from 15 to 22GHz with a nominal 25dB gain and low VSWR 1.15:1 with FBP180 output. The model LB-51-25-ASPO has uniform gain through its frequency span, providing efficient performance characteristics and directionality. Constructed of lightweight corrosion-resistant aluminum, the horn comes with a specially designed weatherproof radome which provides excellent protection against the rain and dust but has very little loss across the full operating frequency band. This standard gain horn antenna is linearly polarized and ideally suited for EMI testing, direction finding, surveillance, antenna gain and pattern measurements and other applications.

Technical Specification


Electrical Specification		Interface	
Frequency, Min (GHz)	15	Output Type	Waveguide
Frequency, Max (GHz)	22	Flange Style	Square
Waveguide Type	Rectangular	Flange Type	Cover
Waveguide Size EIA WR	WR51	Flange Designation	FBP180(UBR180)
Gain, Typ (dBi)	25	Connector Gender	N/A
Polarization	Linear	Mechanical Specification	
3dB Beamwidth, E-Plane, Typ (Deg.)	10	Figure	A Type
3dB Beamwidth, H-Plane, Typ (Deg.)	12	Body Material	Cu
Cross Pol. Isolation, Typ (dB)	40	Finish	Chemical Conversion Coating, Gray Paint
VSWR, Typ	1.15:1	Size, W (mm)	137
		Size, H (mm)	107
		Size, L (mm)	263
		Weight, (kg)	0.72

Additional Information


Application	Outdoor, Waterproof and Dustproof, Fixed	Solution for	Gain Reference Antenna Measurement Reflector Feed Far-field Measurement System Intergration Material Measurement
-------------	--	--------------	---

Outline Drawing

FBP180 Output with Radome (Option, P/N: LB-51-25-ASPO, Outdoor Application)




Flange Drawing




FBP180

Typical Test Results

Gain




Antenna Factor




Antenna Factor (Table)

Frequency(GHz)	Gain(dBi)	Antenna Factor(dB/m)
15.0	22.70	31.30
15.5	22.87	31.15
16.0	23.16	31.13
16.5	23.28	31.28
17.0	23.36	31.46
17.5	23.61	31.46
18.0	23.51	31.80
18.5	23.66	31.89
19.0	23.60	32.19
19.5	23.52	32.49
20.0	23.79	32.44
20.5	23.86	32.58
21.0	23.95	32.70
21.5	23.95	32.91
22.0	23.87	33.19





Cross Polarization Isolation














VSWR



Pattern







Related Products



51WCAS_Cu Right Angle Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to SMA Female



51WCASM_Cu Right Angle Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to SMA Male



51WCA3.5_Cu Right Angle Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to 3.5mm Female



51WCA3.5M_Cu Right Angle Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to 3.5mm Male



51WCAK_Cu Right Angle Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to 2.92mm Female



51WCAKM_Cu Right Angle Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to 2.92mm Male



51WCA2.4_Cu Right Angle Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to 2.4mm Female



51WCA2.4M_Cu Right Angle Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to 2.4mm Male



51WECAS_Cu Endlaunch Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to SMA Female



51WECAK_Cu Endlaunch Rectangular Waveguide to Coaxial Adapter 15-22GHz WR51 to 2.92mm Female



M4x18 Hex_Pack WR112- WR51 Flange Assembly Pack

Similar Products



LB-51-25-A Standard Gain Horn Antenna 15-22GHz 25dB Gain Rectangular Waveguide Interface



LB-51-25-C-SF Standard Gain Horn Antenna 15-22GHz 25dB Gain SMA Female



LB-51-25-C-SFSP Standard Gain Horn Antenna 15-22GHz 25dB Gain SMA Female

About this Datasheet

<ul style="list-style-type: none"> ● Product Information Product Link: https://www.ainfoinc.com/lb-51-25-aspo-standard-gain-horn-antenna-15-22-ghz-25db-gain-fbp180 Data subject to change without notice. © A-INFO INC. 2023. All Rights Reserved 	<ul style="list-style-type: none"> ● Contact Us Address:dd 60 Tesla, Irvine, CA 92618, USA Website: www.ainfoinc.com Email: sales@ainfoinc.com 	<ul style="list-style-type: none"> ● Phone & Fax Phone: +1-949-639-9688 +1-949-639-9608 Fax: +1-949-639-9670
---	--	---