



LB-650-10-C-7/16F Standard Gain Horn Antenna 1.12-1.7GHz 10dB Gain 7/16(DIN) Female

Standard Gain Horn Antenna Operating From 1.12GHz to 1.7GHz With a Nominal 10dB Gain With 7/16(DIN) Female Connector

Product Information

SKU	LB-650-10-C-7/16F
-----	-------------------

Description

Standard Gain Horn Antenna LB-650-10-C-7/16F, operating from 1.12 to 1.7GHz with a nominal 10dB gain and low VSWR 1.25:1 with 7/16(DIN) Female connector output. The model LB-650-10-C-7/16F has uniform gain through its frequency span, providing efficient performance characteristics and directionality. It can handle 500W continuously and 3000W peak power. Constructed of lightweight corrosion-resistant aluminum, the antenna will provide years of trouble-free indoor and outdoor service. This standard gain horn antenna is linearly polarized and ideally suited for EMI testing, direction finding, surveillance, antenna gain and pattern measurements and other applications.

Technical Specification


Electrical Specification		Interface	
Frequency, Min (GHz)	1.12	Output Type	Coaxial
Frequency, Max (GHz)	1.7	Connector	7/16 DIN
Waveguide Type	Rectangular	Connector Gender	Female
Waveguide Size EIA WR	WR650	Mechanical Specification	
Gain, Typ (dBi)	10	Figure	C Type
Polarization	Linear	Body Material	Al
3dB Beamwidth, E-Plane, Typ (Deg.)	48	Finish	Chemical Conversion Coating, Gray Paint
3dB Beamwidth, H-Plane, Typ (Deg.)	45	Size, W (mm)	315
Cross Pol. Isolation, Typ (dB)	35	Size, H (mm)	235
VSWR, Typ	1.25:1	Size, L (mm)	428
Impedance, (Ohm)	50	Weight, (kg)	3.4
Power Handling, CW, (W)	500		
Power Handling, Peak, (W)	3000		

Additional Information


Application	General Purpose Indoor & Outdoor, Fixed	Solution for	Gain Reference Antenna Measurement Reflector Feed Far-field Measurement System Intergration Material Measurement
-------------	---	--------------	---

Outline Drawing


7/16(DIN) Female Output (P/N: LB-650-10-C-7/16F)



7/16(DIN) Female Output with Round Mounting Bracket (Option, P/N: LB-650-10-C-MB)




7/16(DIN) Female Output with L Type Mounting Bracket (Option, P/N: LB-650-10-C-L)




Typical Test Results

Gain




Antenna Factor




Antenna Factor (Table)

Frequency(GHz)	Gain(dBi)	Antenna Factor(dB/m)
1.1	8.9	22.14
1.2	10.0	21.79
1.3	10.8	21.69
1.4	11.5	21.63
1.5	12.0	21.73
1.6	12.7	21.59
1.7	13.3	21.52



Cross Polarization Isolation




VSWR



Pattern





Related Products



LB-650-10-C-MB Round Type Mounting Bracket



LB-650-10-C-L L type mounting bracket



Tripod_50Kg Al Alloy Tripod




Carrying Case_LB-650-10-C Al Alloy Carrying Case



M8x40 Hex_Pack WR510-WR650 Flange Assembly Pack

Similar Products



LB-650-10-A Standard Gain Horn Antenna 1.12-1.7GHz 10dB Gain Rectangular Waveguide Interface



LB-650-10-ASPO Standard Gain Horn Antenna 1.12-1.7GHz 10dB Gain Rectangular Waveguide Interface



LB-650-10-C-NF Standard Gain Horn Antenna 1.12-1.7GHz 10dB Gain N Type Female




LB-650-10-C-NFSPO Standard Gain Horn Antenna 1.12-1.7GHz 10dB Gain N Type Female



LB-650-10-C-SF Standard Gain Horn Antenna 1.12-1.7GHz 10dB Gain SMA Female



LB-650-10-C-SFSPO Standard Gain Horn Antenna 1.12-1.7GHz 10dB Gain SMA Female



LB-650-10-C-7/16FSPO Standard Gain Horn Antenna 1.12-1.7GHz 10dB Gain 7/16(DIN) Female

About this Datasheet

● Product Information Product Link: https://www.ainfoinc.com/lb-650-10-c-7-16f-standard-gain-horn-antenna-1-12-1-7-ghz-10db-gain-7-16-din-female Data subject to change without notice. © A-INFO INC. 2023. All Rights Reserved	● Contact Us Address:dd 60 Tesla, Irvine, CA 92618, USA Website: www.ainfoinc.com Email: sales@ainfoinc.com	● Phone & Fax Phone: +1-949-639-9688 +1-949-639-9608 Fax: +1-949-639-9670
--	--	--