MINI DIGITAL CLAMP TESTER

AC CURRENT/LEAKAGE

Model 110

2mA/20mA/60A 30㎜φ CT

FEATURES

- Model 110 is a clamp-on type ammeter which is least affected by external magnetic fields.
- 30㎜φCT enables the leakage current measurement for SV cable (38m)
- Data hold function.Especially useful when working in dark or hard to get areas.
- Pocket sized and light weight.

SPECIFICATIONS

Measuring method : Dual integration mode
Display : 3.5 digit LCD, max.reading of 1999
Range : 0～2mA/20mA/60A (50/60Hz)
Ranging : Manual ranging
Accuracy : 50/60Hz, 23℃±5℃, 80% RH max

Range	Mini.Resolution	Accuracy
2mA	1μA	±1.0% rdg ±5 dgt
20mA	10μA	
60A	100mA	±1.0% rdg ±5 dgt(0～50A) ±5% rdg ±5 dgt (50A～60A)

Jaw opening capability : 30㎜φ
Over range indication : Blanking of all digits except MSD1
Maximum indication : 1999
Low battery indication : "B"mark on LCD readout
Data hold indication : "DH"mark on LCD readout
Sampling : Approx. 2 times/s.
Limitation of circuit voltage : Less than AC 600V
Operating temperature : 0℃ to 40℃,<70% RH (Non-condensing)
Storage temperature : -10℃to 60℃,<70%RH (Non-condensing)
Power supply : LR-44 or SR-44×2
Power consumption : Approx.3mW
Battery Life : Approx.100 hours (LR-44)
Approx.200 hours (SR-44)
Size : 58.5(W)×158(H)×23(D)㎜
Weight : Approx.120g
Accessories : Batteries (LR-44) ····· 2
Instruction manual ····· 1
Carrying case ····· 1

НАУЧНОЕ ОБОРУДОВАНИЕ
ГРУППА КОМПАНИЙ