

HUBER+SUHNER® DATA SHEET

RF TERMINATION: Type 65_SMA-50-0-1/111_N



Rev.: 0

Description

Standard Termination, Low Power

Product Configuration

Connector SMA plug (male)
Interface standard IEC 60169-15_MIL-STD-348A/310_CECC 22110



Technical Data

Electrical Data

Nominal impedance 50 Ω
Frequency range DC to 18 GHz
Frequency sub range (GHz) DC to 4 4 to 10 10 to 14 14 to 18
VSWR max. 1.05 1.1 1.15 1.25
Power rating 1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient temperature.
500 Watt peak power

Mechanical Data

Weight 0.0033 kg

Environmental Data

Operating temperature -55 °C to 130 °C
Water and dust resistance IP 68 (1m, 24h), (according to IEC 60529, data refer to the coupled state)
2002/95/EC (RoHS) compliant

Material Data

Piece Part

Centre contact Copper Beryllium Alloy
Outer contact Copper Beryllium Alloy
Body Copper Beryllium Alloy
Insulator PFA / PTFE
Coupling nut Bronze

Surface Plating

Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)
Gold Plating (Nickel underplated)

Related Documents

Outline drawing DOU-00064214

Ordering Information

Single packaging 65_SMA-50-0-1/111_NE
Bulk 100 pcs packaging 65_SMA-50-0-1/111_NH

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!

It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER – Excellence in Connectivity Solutions

Document: DOC-0000222973 AB

Issued: 29.03.10



HUBER+SUHNER AG
RF Industrial
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com



Uncontrolled Copy Page 1/1