

## Analog Clamp Tester

AC Current ,6A/15A/50A/150A/600A  
40mm  $\phi$  CT

**Model 3000 (CE)**



### *FEATURES*

- High accuracy analog display with strong taut band meter.
- Meter lock function.
- AC current ,AC/DC voltage and resistance measurements.
- Conform to IEC safety requirements.

## ***SPECIFICATIONS***

Safety standard	: IEC 61010-1, IEC 61010-2-032 ,Installation Category III 600V phase to earth.
E.M.C. standard	: EN 61326.
Display	: Analog taut band meter
Jaw opening capability	: 40mm $\phi$
Current range	: AC 0~6A/15A/50A/150A/600A
Accuracy	: $\pm 3\%$ of full scale(50/60Hz)
Voltage range	: AC 0~300V/600V DC 0~60V
Accuracy	: $\pm 3\%$ of full scale(50/60Hz)
Resistance range	: 0~1k $\Omega$ /100k $\Omega$ (50 $\Omega$ /5k $\Omega$ center)
Accuracy	: $\pm 3\%$ of scale length
Temperature	: -50°C to 200°C (Optional thermister sensor)
Withstanding voltage	: AC 5500V 1 minute max. (Between the core of CT and outer case)
Operating temperature	: 0°C to 40°C, 80%RH max. ( Without condensation )
Storage temperature	: -10°C to 60°C, 70%RH max. ( Without condensation )
Power supply	: 1.5V (AM-4,LR03 or AAA) $\times$ 2
Size	: 69(W) $\times$ 210(H) $\times$ 34(D)mm
Weight	: Approx. 400g
Accessories	: Hard carrying case.....1 Instruction manual.....1 Test lead.....1set Batteries.....2
Option	: MT-3000 thermister sensor probe