


# Generation of induced voltage with a permanent magnet

(Item No.: P1433602)

## Curricular Relevance



### Difficulty



Intermediate

### Preparation Time



10 Minutes

### Execution Time



20 Minutes

### Recommended Group Size



2 Students

### Additional Requirements:

### Experiment Variations:


- P1398900 on the magnetic board
- P1433602 with a demonstration coil

### Keywords:

## Introduction

### Overview

The generation of induction voltages by a permanent magnet is to be demonstrated, and the conditions which govern the size of them are to be investigated



## Equipment

Position No.	Material	Order No.	Quantity
1	Coil, 300 turns	06513-01	1
2	Coil, 1200 turns	06515-01	1
3	Bar magnet, l = 72mm	07823-00	1
4	Connecting cord, 32 A, 500 mm, red	07361-01	1
5	Connecting cord, 32 A, 500 mm, blue	07361-04	1
6	Multimeter ADM2, demo., analogue	13820-01	1

## Set-up and procedure

- Set up the experiment as shown in Fig. 1
- Set the 10-0-10 m V measurement range
- Carry out the following experimental steps successively, in each case under observance of the deflection of the pointer of the voltage measuring instrument (galvanometer); enter each observation in the pre-prepared Table 1.

Note: The movements in steps 1 to 4, and also step 8, should be carried out at as near the same speed as possible.

1. Move the magnet into the coil with the north pole foremost
2. Remove the magnet from the coil
3. Move the magnet into the coil with the south pole foremost
4. Remove the magnet from the coil
5. Move the magnet quicker into and out of the coil
6. Leave the magnet still in the coil
7. Rotate the magnet lengthwise in the coil
8. Replace the 400 turn coil with the 1600 turn coil and proceed according to steps i and 2

## Evaluation

### Observations

Movement	Pointer deflection (to the left/right, greater/less)
1. North pole into the coil	to the right
2. North pole out of the coil	to the left
3. South pole into the coil	to the left
4. South pole out of the coil	to the right
5. Quicker movement of the magnet	greater
6. Magnet at rest in the coil	no deflection
7. Magnet rotated lengthwise	no deflection
8. As 1 . to 4. with 1600 turn coil	greater

From the results found in steps 1 to 6, it is clear that a voltage is generated, as long as the magnet and the coil are moved relative to one another. As step 7 shows, the movement must be so that magnetic field that is spanned by the coil is changed. We therefore have: A voltage will be induced in a coil as long as the magnetic field spanned by the coil is changed. The direction of the induced voltage depends on whether the magnet is moved into it or out of it, and which pole of the magnet is directed towards the coil. The induction voltage is higher the quicker the movement takes place and the more turns the induction coil has. In induction, mechanical energy is converted to electrical energy. This is the basis of the mode of action of a generator. The process is called electromagnetic induction.

## Remarks

The entries in Table 1 have only been made as examples. The observations made in the experiment are dependent on how the voltmeter is connected.